





## Related Products and Services

- ▶ **Omni-ID IQ 600** - Ultrathin label providing on metal tag functionality, low cost and hassle free deployment.
- ▶ **Omni-ID Flex 600** - Low profile, cost effective tag, ideal for office equipment and portal setups.
- ▶ **Omni-ID Flex 1600** - Low cost alternative to hard tags for applications requiring read ranges up to 16 meters.
- ▶ **Service Bureau** - Omni-ID offers a full service bureau for printing and pre-encoding Omni-ID tags at point of manufacture.



## Environmental Specifications

|                                    |   |
|------------------------------------|---|
| Storage Temperature                | -40 ° to +85 °C   |
| Operation Temperature <sup>1</sup> | -40 ° to +85 °C   |
| Survivability                      | -40 ° to +85 °C   |
| IP Rating                          | IP68  |
| Shock and Vibration                | MIL STD 810-G   |
| Attachment                         | Film adhesive (std)   |
| Certifications                     | RoHS approved<br>CE approved<br>US&Canada (C1D1/D2) certified (option)  |
|                                    |   |
| Warranty                           | 1 year  |

<sup>1</sup> Excludes adhesive options, consult adhesive data sheets for recommended temperature ratings.

## Ordering Information

|               |  |
|---------------|--|
| Order code    | 160 - EU, US   |
| Order options | :303 (Customization)<br>:307 (US&Canada (C1D1/D2) certified) |

Supplied in rolls of 900 tags. Minimum order quantity is 1 roll.