

June 2021

# Belt U9

## Overview

---

**Frequency Band**

UHF 860 - 960 MHz

---

**Chip**

NXP UCODE 9

---

**Antenna Dimensions**

70 x 14 mm / 2.75 x 0.55 in

---

**International Standard**

ISO 18000-63, EPC Class 1 Gen 2

---

**Industry Segments**

Apparel  
Industrial Applications

---

**Applications**

Brand Protection  
Supply Chain Management  
Home Essentials

---

**RoHS**

EU Directive 2011/65/EU and  
Directive (EU) 2015/863

---

**REACH**

Regulation (EC) No. 1907/2006



## Compact size and high performance in item-level tagging

Our Belt inlays and tags are designed for global retail, industry and supply-chain applications, offering excellent performance on difficult-to-tag or low-detuning materials such as cardboard and plastic, and in other demanding, close-coupling environments.

Belt inlays and tags have a compact 73 mm / 2.8 inch form factor, which can be easily converted into end-application usage, and are available in dry, wet and label / sticker delivery formats. Belt equipped with NXP UCODE 9 offers 96-bit of EPC memory. Furthermore, it offers a self adjust feature to maximize product performance in challenging environments and has an improved read and write sensitivity and faster encoding speed compared to NXP UCODE 8.

Belt with the NXP UCODE 9 IC, used in retail applications, is included on the approved inlay list by the RFID Research Center at the University of Auburn, and complies with categories F, G, I, K, M, N, L, Q, W1, W2, W3, W4, W5 and W6.


Avery Dennison inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, especially in the retail environment.

June 2021


## Technical features

Chip	NXP UCODE 9		
EPC and User Memory	96-bit and n/a		
TID Memory	96-bit / 48-bit unique serial number		
Product Code	3008008	3008009	3008010
Delivery Format	Dry inlay	Wet inlay	Label / sticker
Die-Cut Dimension	-	73 x 17 mm / 2.87 x 0.67 in	73 x 17 mm / 2.87 x 0.67 in
Inlay Substrate	PET	PET	PET
Face Sheet	-	PET	Mid-gloss paper
Standard Pitch	20 mm / 0.787 in	20 mm / 0.787 in	20 mm / 0.787 in
Web Width	80 mm / 3 in	80 mm / 3 in	80 mm / 3 in
Core Size	76 mm / 3 in	76 mm / 3 in	76 mm / 3 in
Quantity / Reel	20,000 pcs/reel 40,000 pcs/box	20,000 pcs/reel 40,000 pcs/box	5,000 pcs/reel 10,000 pcs/box
Operating Temperature	-40 °C to 85 °C / -40 °F to 185 °F		
Certificate	ARC		

## Orientation sensitivity



## Read range



All graphs are indicative: performance in real life applications may vary.



© 2021 Avery Dennison Corp. All rights reserved. 170 Monarch Lane, Miamisburg, OH 45342, USA Third party trademarks and/or trade names used herein are the property of their respective owner(s). Some of the trademarks appear for identification purposes only.

**Warranty:** Please refer to Avery Dennison standard terms and conditions: [rfid.averydennison.com/termsandconditions](http://rfid.averydennison.com/termsandconditions)

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

