





DOGBONE® DURA

Adding Robustness to Excellent Performance on Demanding Applications

Smartrac's DOGBONE® DURA RAIN RFID (UHF) inlays and tags combine excellent performance on different materials with outstanding robustness and water resistance, making them an excellent choice for demanding global supply chain and industrial applications in harsh environments.

DOGBONE DURA comes with thick, semi-stiff thermosetting layers attached to both sides of the antenna/IC structure, providing effective protection against mechanical and environmental stresses without affecting the performance of the underlying inlay design. Moreover, the encasement provides an IP68 rating and is ATEX compatible, making DOGBONE DURA certifiable for ATEX upon request

Tested to EN60068-2-27 (mechanical shock) and EN60068-2-6 (vibration) standards, DOGBONE DURA provides a level of durability that is comparable to hard tags while retaining its advantages in terms of cost efficiency, flexibility (reel format available) and weight.

DOGBONE DURA is available with the Impinj Monza R6-PIC that comes with an Autotune feature, which helps the DOGBONE product to work at peak efficiency, even in rapidly changing environments. DOGBONE DURA's IC enables pre-serialized EPC and offers unique TID as well as other features.

DOGBONE DURA has a white printable face material and available in wet and dry formats. Wet format tags come with water-resistant high-strength adhesive, while dry format tags have extensions to allow a punch hole for attachment.

Smartrac's inlays and tags are compliant with ISO 9001:2015 Quality Manage- ment and ISO 14001:2015 Environmental Management, which ensure a reliable and state-of-the-art product that meets a variety of application needs, enhancing RFID usage for difficult-to-tag materials.

Overview

Operating Frequency

860 - 960 MHz

Integrated Circuit (IC)

Impinj Monza R6-P

Antenna Size

 $94 \times 24 \text{ mm} (3.7 \times 0.9 \text{ in})$

Die-cut Size

 $127 \times 27 \text{ mm} (5.0 \times 1.0 \text{ in})$

International Standards

▶ EPC Class 1 Gen 2 ISO 18000-6C

Application Areas

- Industrial Applications
- Logistics
- ▶ Returnable Transport
- ▶ Waterproof Applications





DOGBONE® DURA

Adding Robustness to Excellent Performance on Demanding Applications

| Size | Format | Sales Code | Reel Size |
|---|---|---|--|
| $94 \times 24 \text{ mm} / 3.7 \times 0.9 \text{ in}$ | Dry | 3006914 | 1,000 |
| $94 \times 24 \text{ mm} / 3.7 \times 0.9 \text{ in}$ | Wet | 3006915 | 1,000 |
| 130 mm / 5.118 in | | | |
| -40 °C to +85 °C / -40 °F to +185 °F | | | |
| RA-25 | | | |
| 2,000 pcs/box | | | |
| +20 °C, 50 % RH 68 °F, 50 % R | H from the date of manu | facture 2 years | |
| | 94×24 mm / 3.7×0.9 in 94×24 mm / 3.7×0.9 in 130 mm / 5.118 in -40 °C to +85 °C / -40 °F to +18 RA-25 2,000 pcs/box | 94×24 mm / 3.7×0.9 in Dry 94×24 mm / 3.7×0.9 in Wet 130 mm / 5.118 in -40 °C to +85 °C / -40 °F to +185 °F RA-25 2,000 pcs/box | 94 × 24 mm / 3.7 × 0.9 in Dry 3006914 94 × 24 mm / 3.7 × 0.9 in Wet 3006915 130 mm / 5.118 in -40 °C to +85 °C / -40 °F to +185 °F RA-25 |



